

Nickel 205 (UNS N02205) is wrought nickel similar to Nickel 200 but with compositional adjustments to enhance performance in electrical and electronic applications. Nickel 205 is used for the anodes and grids of electronic valves, magnetostrictive transducers, lead wires, transistor housings and battery cases.

Physical Constants & Thermal Properties

Table 2 - Physical Constants & Thermal Properties

Density, lb/in ³	0.321
g/cm ³	8.89
Melting Range, °F.....	2615-2635
°C	1435-1446
Specific Heat, Btu/lb•°F	0.109
J/kg•°K	456
Curie Temperature, °F.....	680
°C	360
Permeability.....	Ferromagnetic
Coefficient of Expansion, 70-200°F, 10 ⁻⁶ in/in•°F.....	7.4
21-93°C, µm/m•°C	13.3
Thermal Conductivity, Btu•in/ft ² •h•°F	520
W/m•°C	75.0
Electrical Resistivity, ohm•circ mil/ft	57
µohm•m.....	0.095

Table 1 - Limiting Chemical Composition, %

Nickel (Plus Cobalt)	99.0 min.
Magnesium.....	0.01-0.08
Titanium.....	0.01-0.05
Copper	0.15 max.
Iron.....	0.20 max.
Carbon	0.15 max.
Silicon	0.15 max.
Sulfur.....	0.008 max.
Manganese	0.35 max.

Typical Mechanical Properties

Table 3 - Typical Mechanical Properties of Annealed Nickel 205

Tensile Strength, ksi.....	.50
MPa.....	345
Yield Strength (0.2% Offset), ksi	13
MPa	90
Elongation, %	45

Available Products and Specifications

Nickel 205 is designated UNS N02205 and is available as sheet, strip and wire.

Major specifications:

ASTM F 1, F 3
SAE AMS 5555